

## IP ACCESS ROUTER



Universal VPN-router with VDSL2/ ADSL2+ and 11n WIFI

### **bintec RS353aw**

- VDSL2/ ADSL2+ Modem (Annex A)
- WIFI 802.11n, 2,4 and 5 GHz
- Vectoring ready
- 5x IPSec-tunnels (optional 30 tunnels), HW acceleration
- Prepared for IPv6
- Flexible mounting: Desktop or 19" Rack
- Stateful Inspection Firewall



## bintec RS353aw

### Universal VPN-router with VDSL2/ ADSL2+ and 11n WIFI

The bintec RS353a with its combined VDSL/ADSL2+ Modem (Annex A) and dual band WIFI (802.11n) is ideal for use in home offices and at small branch locations.

#### Product description

The bintec RS353aw is a powerful professional VPN router for high-speed internet access. With its combination VDSL2 and ADSL 2+ modem, this model gives small and mid-sized companies the foundation they need to establish state-of-the-art, robust internet connectivity. The integrated 802.11n wireless module also provides wireless data connectivity for enterprise applications.

The RS353aw delivers advanced security, flexibility, and exceptional performance across a wide range of applications. The combination VDSL2 and ADSL2+ modem supports the Annex A standard (ADSL over POTS) according to ITU standard G992.1. The system also has a state-of-the-art dual-band wireless module which operates at 2.4 and 5 GHz. This module supports all current wireless standards including 802.11 a/b/g/n. The MIMO 2x2 technology allows for maximum raw data rates of up to 300 Mbps.

This router boasts a fan-less metal housing, offers long-term reliability for business-critical applications, and makes an ideal access router for small and mid-sized enterprises (SMEs), branch locations, and home offices.

Thanks to the included 19-inch rackmount conversion bracket, customers can easily integrate this model into 19-inch server racks or operate it on the desktop. Rack mounting is further simplified by the device height of exactly one rack unit and the integrated power supply.

In addition to the VDSL2 /ADSL2+ modem, the bintec RS353aw also provides five Gigabit Ethernet ports which can be independently configured for use in a LAN, WAN, or DMZ. The included five licenses for hardware-accelerated IPSec tunnels provide comprehensive high-speed VPN functionality and allow for secure connections to branch locations and off-site employees. An LTE(4G) or UMTS(3G) USB modem (stick) connected to the USB port can be used as a remote configuration access and as a backup interface.

With its wide range of WAN connectivity options, the RS353aw raises the bar for flexibility among access routers.

#### Smart design

The fan-free metal housing is a proven, rugged design that has set bintec devices apart from the competition for years. The integrated power supply and 19" conversion bracket now also make it easy to install in a 19" rack.

#### Maximum performance

The bintec RS353aw is based on a powerful platform with unrivaled capabilities. Customers with VDSL2 connections can double their data transfer rates by taking advantage of VDSL vectoring technology. High speed interfaces handle heavy local network traffic with ease.

## **Airtight security**

The bintec RS353aw not only delivers outstanding performance, it also provides a comprehensive range of security features. With five simultaneous IPSec channels available, you can establish secure links between branch locations, subsidiaries, and home offices. Optional the quantity of VPN tunnels can be extended to 30 tunnels. The integrated IPSec implementation in bintec routers allows the use of pre-shared keys as well as digital certificates as recommended by Germany's Federal Office for Information Security. This lets you use a public key infrastructure and ensures maximum security. An object-oriented stateful inspection firewall offers packet filtering to provide additional protection against attacks.

## **Professional management**

A graphical user interface is the primary means of configuring the router. This fast, web-based interface makes it easy to set up routers using the integrated configuration wizard. Administrators can also manage the devices locally or remotely using configurable telnet, SSH, or GSM dial-in. The bintec DIME Manager is a free software tool that allows administrators to manage up to 50 devices at once.

## **Ready for the future**

Businesses can easily integrate the RS353aw into existing company networks. This bintec router also allows for a gradual migration to the new IPv6 internet protocol. The integrated VDSL2 modem of the bintec RS353aw supports the asymmetric VDSL bandplan 998 including profiles 8b, 17a, and 30a, the standards used in Germany and most other European countries. The modem also supports automatic failover to ADSL2+. With easy migration from ADSL2+ to VDSL2 and support for VDSL vectoring, the professional-grade bintec RS353aw router is a sound investment in your organization's future.

## **WLAN Controller, HotSpot and adult content filtering**

The router also includes all the functionality of the bintec WLAN Controller. The bintec WLAN controller lets you configure and monitor small- and mid-sized WLAN networks with up to 12 access points. No matter whether you need frequency management with automatic channel selection, loadbalancing across several access points, support for virtual LANs, or virtual wireless network administration (multi-SSID) - you have all these advanced features at your fingertips with the WLAN Controller. The software continually monitors the entire wireless network, notifying administrators of any malfunctions or security threats.

The router's integrated HotSpot Gateway together is an ideal complement to the WLAN Controller in combination with a bintec HotSpot license, allowing operators to set up a wireless guest network that requires authentication. This secure separation between the guest network and company network is configured through the WLAN Controller and implemented using virtual wireless networks. An additional highlight is the optional Cobion filter which can be used to prevent children and youth from accessing inappropriate content.

## Variants

<b>bintec RS353aw-UK</b> (5510000365)	IP Access Router; Desktop device with 19"Rack; incl. VDSL2(opt.)/ADSL modem (Annex A,POTS); 11n WLAN; 5 IPSec tunnel (opt.30), certificates, HW encryption; 4+1 Gbit Eth.switch; USB (Typ B); USB port; no use with Deutsche Telekom equipment; UK Version
<b>bintec RS353aw</b> (5510000344)	IP Access Router; Desktop device with 19"Rack; incl. VDSL2(opt.)/ADSL modem (Annex A,POTS); 11n WLAN; 5 IPSec (opt.30), certificates, HW encrypt.; 4+1 Gbit Eth.switch; USB (TypB); USB port; no use with Deutsche Telekom equip.; german & intern.version

## Features

DSL	
ADSL 2 / ADSL 2+	ADSL over POTS (ITU G.992.1, ITU G.922.2, ITU G.992.3, ITU G.992.5 Annex A)
VDSL Vectoring	Vectoring ready by ITU-T G.993.5
VDSL	Backward compatible to ADSL/ADSL2/ADSL2+ over POTS, Annex A
VDSL	VDSL2 ITU G.993.2
VDSL Profile	VDSL Profile 8a, 8b, 8c, 8d, 12a, 12b, 17a, 30a
ADSL	Support of Dying Gasp
ATM	Support of layer 1 protocol AAL5, PVCs, RFC 1483
ATM	Support of up to 7 virtual channels (VC)
ATM	Support of OAM F4/F5 line monitoring
ATM	Support of ATM traffic management (COS - CBR, VBR, UBR)

Wireless LAN	
Advanced 11n performance features	Beamforming, MRC (Maximum Ratio Combining), Block-Acknowledge
Number of spatial streams (802.11n)	1 or 2
Transmission rate	Automatic fallback or fixed transmission rate selectable
Multi SSID	Depending on the complexity of configuration up to 8 service sets per radio module, with virtual access points and own MAC address per SSID.
Broadcast SSID	On/off switchable
Bandwidth (802.11n)	20/40 MHz (bundling of two adjoining 20 MHz channels to one 40 MHz channel)
RTS/CTS	RTS/CTS threshold adjustable
Short guard interval (802.11n)	On/off switchable; increase of throughput by reduction of the guard intervals from 800ns to 400ns
DTIM Period	Adjustable

## Wireless LAN

WLAN standards	802.11n (Mimo 2x2); 802.11b; 802.11g; 802.11a; 802.11h
Frequency bands 2.4 GHz indoor/outdoor (EU)	2.4 GHz Indoor/Outdoor (2412-2472 MHz) max. 100 mW EIRP. The permitted transmission power may vary in countries outside the EC.
Frequency bands 5 GHz indoor (EU)	5 GHz indoor (5150-5350 MHz) max. 200 mW EIRP allowed (Germany). The permitted transmission power may vary in other countries.
Frequency bands 5 GHz outdoor (EU)	5 GHz outdoor (5470-5725 MHz) max. 200 mW EIRP allowed (Germany). The permitted transmission power may vary in other countries.
WLAN operation	WLAN Accesspoint operation
WLAN modes	2.4 GHz operation: 802.11b only; 802.11g only, 802.11b/g/n mixed; 802.11b/g/n mixed long; 802.11b/g/b mixed short; 802.11b/g/n; 802.11g/n; 802.11n only; 5 GHz Operation: 802.11a only; 802.11a/n; 802.11n only
Automatic Rate Selection (ARS)	Automatic usage of the optimized data rate
Data rates for 802.11b,g (2.4 GHz)	11, 5.5, 2 und 1 Mbps (DSSS modulation); 54, 48, 36, 24, 18, 12, 9 and 6 Mbps (OFDM modulation)
Data rates for 802.11a,h (5 GHz)	54, 48, 36, 24, 18, 12, 9 and 6 Mbps (OFDM modulation)
Data rates for 802.11n (2.4 / 5 GHz)	MCS0-15 enables physical rates up to 150 Mbps at 20 MHz channels bandwidth, 2 streams, short guard interval; MCS0-15 enables physical data rates up to 300 Mbps at 40 MHz channels bandwidth, 2 streams, short guard interval

## WLAN Electric Characteristics

TX power @ 5 GHz 802.11n 40 MHz	MCS0/8 19 dBm; MCS1/9 19 dBm; MCS2/10 19 dBm; MCS3/11 19 dBm; MCS4/12 19 dBm; MCS5/13 18 dBm; MCS6/14 17 dBm; MCS7/15 17 dBm
Receiver Sensitivity @ 5 GHz 802.11n 20 MHz	MCS0 -96 dBm; MCS1 -93 dBm; MCS2 -91 dBm; MCS3 -88 dBm; MCS4 -85 dBm; MCS5 -81 dBm; MCS6 -79 dBm; MCS7 -77 dBm; MCS8 -94 dBm; MCS9 -92 dBm; MCS10 -90 dBm; MCS11 -87 dBm; MCS12 -84 dBm; MCS13 -80 dBm; MCS14 -78 dBm; MCS15 -76 dBm
TX power @ 5 GHz 801.11a/h	6 Mbps 19 dBm; 9 Mbps 19 dBm; 12 Mbps 19 dBm; 18 Mbps 19 dBm; 24 Mbps 19 dBm; 36 Mbps 19 dBm; 48 Mbps 19 dBm; 54 Mbps 19 dBm
Receiver Sensitivity @ 2.4 GHz 802.11n 20 MHz	MCS0 -95 dBm; MCS1 -94 dBm; MCS2 -92 dBm; MCS3 -88 dBm; MCS4 -85 dBm; MCS5 -81 dBm; MCS6 -80 dBm; MCS7 -78 dBm; MCS8 -95 dBm; MCS9 -94 dBm; MCS10 -91 dBm; MCS11 -87 dBm; MCS12 -84 dBm; MCS13 -81 dBm; MCS14 -79 dBm; MCS15 -77 dBm
Receiver Sensitivity @ 2.4 GHz 802.11b/g	1 Mbps -92 dBm; 2 Mbps -92 dBm; 5,5 Mbps -92 dBm; 11 Mbps -92 dBm; 6 Mbps -95 dBm; 9 Mbps -95 dBm; 12 Mbps -94 dBm; 18 Mbps -92 dBm; 24 Mbps -90 dBm; 36 Mbps -85 dBm; 48 Mbps -83 dBm; 54 Mbps -80 dBm
TX power @ 2,4 GHz 801.11b/g	1 Mbps 19 dBm; 2 Mbps 19 dBm; 5,5 Mbps 19 dBm; 11 Mbps 19 dBm; 6 Mbps 19 dBm; 9 Mbps 19 dBm; 12 Mbps 19 dBm; 18 Mbps 19 dBm; 24 Mbps 19 dBm; 36 Mbps 19 dBm; 48 Mbps 19 dBm; 54 Mbps 19 dBm
Receiver Sensitivity @ 5 GHz 802.11n 40 MHz	MCS0 -91 dBm; MCS1 -89 dBm; MCS2 -87 dBm; MCS3 -84 dBm; MCS4 -81 dBm; MCS5 -78 dBm; MCS6 -76 dBm; MCS7 -74 dBm; MCS8 -90 dBm; MCS9 -89 dBm; MCS10 -87 dBm; MCS11 -83 dBm; MCS12 -80 dBm; MCS13 -77 dBm; MCS14 -75 dBm; MCS15 -73 dBm
TX power @ 5 GHz 802.11n 20 MHz	MCS0/8 23 dBm; MCS1/9 23 dBm; MCS2/10 22 dBm; MCS3/11 21 dBm; MCS4/12 20 dBm; MCS5/13 19 dBm; MCS6/14 18 dBm; MCS7/15 18 dBm



## WLAN Electric Characteristics

Receiver Sensitivity @ 2.4 GHz 802.11n 40 MHz	MCS0 -92 dBm; MCS1 -91 dBm; MCS2 -89 dBm; MCS3 -86 dBm; MCS4 -82 dBm; MCS5 -79 dBm; MCS6 -77 dBm; MCS7 -75 dBm; MCS8 -91 dBm; MCS9 -91 dBm; MCS10 -89 dBm; MCS11 -85 dBm; MCS12 -82 dBm; MCS13 -78 dBm; MCS14 -77 dBm; MCS15 -74 dBm
Receiver Sensitivity @ 5 GHz 802.11a/h	6 Mbps -95 dBm; 9 Mbps -94 dBm; 12 Mbps -93 dBm; 18 Mbps -90 dBm; 24 Mbps -88 dBm; 36 Mbps -84 dBm; 48 Mbps -82 dBm; 54 Mbps -81 dBm
TX power @ 2,4 GHz 802.11n 20 MHz	MCS0/8 19 dBm; MCS1/9 19 dBm; MCS2/10 19 dBm; MCS3/11 19 dBm; MCS4/12 19 dBm; MCS5/13 19 dBm; MCS6/14 19 dBm; MCS7/15 19 dBm
TX power @ 2,4 GHz 802.11n 40 MHz	MCS0/8 19 dBm; MCS1/9 19 dBm; MCS2/10 19 dBm; MCS3/11 19 dBm; MCS4/12 19 dBm; MCS5/13 19 dBm; MCS6/14 19 dBm; MCS7/15 19 dBm

## Routing

Multicast IGMP	Support of Internet Group Management Protocol (IGMP v1, v2, v3) for the simultaneous distribution of IP packets to several stations
Multicast IGMP Proxy	For easy forwarding of multicast packets via dedicated interfaces
Policy based Routing	Extended routing (Policy Based Routing) depending of different criteria like IP protocols (Layer4), source/destination IP address, source/destination port, TOS/DSCP, source/destination interface and destination interface status
Multicast inside IPSec tunnel	Enables the transmission of multicast packets via an IPSec tunnel
RIP	Support of RIPv1 and RIPv2, separated configurable for each interface
Extended RIP	Triggered RIP updates according RFC 2091 and 2453, Poisoned Reverse for a better distribution of the routes; furthermore the possibility to define RIP filters for each interface.

## Protocols / Encapsulations

DNS	DNS client, DNS server, DNS relay and DNS proxy
PPP/MLPPP	Support of Point to Point Protocol (PPP) for establishing of standard PPP connections, inclusive the Multilink extension MLPPP for the bundeling of several connections
IPoA	Enables the easy routing of IP via ATM
PPPoE (Server/Client)	Point-to-Point Protocol over Ethernet (Client and Server) for establishing of PPP connections via Ethernet/DSL (RFC 2516)
DNS Forwarding	Enables the forwarding of DNS requests of free configurable domains to assigned DNS server.
MLPPPoE (Server/Client)	Multilink extension MLPPPoE for bundeling several PPPoE connections (only if both sides support MLPPPoE)
DYN DNS	Enables the registering of dynamic assigned IP addresses at a dynamic DNS provider, e.g. for establishing of VPN connections
DHCP	DHCP Client, Server, Proxy and Relay for simplified TCP/IP configuration
PPPoA	Point to Point Protocol over ATM for establishing of PPP connections via ATM/DSL
Packet size controlling	Adaption of PMTU or automatic packet size controlling via fragmentation

## Quality of Service (QoS)

Layer2/3 tagging	Conversion of 802.1p layer 2 prioritisation information to layer 3 diffserv attributes
DiffServ	Priority Queuing of packets on the basis of the DiffServ/TOS field
Bandwidth reservation	Dynamic reservation of bandwidth, allocation of guaranteed and maximum bandwidths
TCP Download Rate Control	For reservation of bandwidth for VoIP connections
Policy based Traffic Shapping	Dynamic bandwidth management via IP traffic shaping
Warranty	2 year manufacturer warranty inclusive advanced replacement
Software Update	Free-of-charge software updates for system software (BOSS) and management software (DIME Manager)

## Redundancy / Loadbalancing

BoD	Bandwidth on Demand: dynamic bandwidth to suit data traffic load
VPN backup	Simple VPN backup via different media. Additional enables the bintec elmeg interface based VPN concept the application of routing protocols for VPN connections.
Load Balancing	Static and dynamic load balancing to several WAN connections on IP layer
BRRP	Optional: Bintec Router Redundancy Protocol for backup of several passive or active devices with free selectable priority

## Layer 2 Functionality

Bridging	Support of layer 2 bridging with the possibility of separation of network segment via the configuration of bridge groups
VLAN	Support of up to 256 VLAN (Virtual LAN) for segmentation of the network in independent virtual segments (workgroups)
Proxy ARP	Enables the router to answer ARP requests for hosts, which are accessible via the router. That enables the remote clients to use an IP address from the local net.

## Interfaces

VDSL2/ ADSL 2+/ ADSL	xDSL over POTS
Ethernet	5 x 10/100/1000 Mbps Ethernet Twisted Pair, autosensing, Auto MDI/MDI-X, up to 4 ports can be switches as additional WAN ports incl. load balancing, all Ethernet ports can be configured as LAN or WAN.
USB 2.0 host	USB 2.0 full speed host port for connecting LTE(4G) or UMTS(3G) USB sticks (supported sticks: see <a href="http://www.bintec-elmeg.com">www.bintec-elmeg.com</a> )
USB-Console	Service-Interface USB 2.0 plug B (driver: see <a href="http://www.bintec-elmeg.com">www.bintec-elmeg.com</a> )

## Hardware

Status LEDs	Power, Status, 10 * Ethernet, VDSL, WLAN, USB
-------------	---

## Hardware

Realtime clock	System time persists even at power failure for some hours.
Wall mounting	Integrated in housing
Desktop operation	Possible, rubber pad included the package
Environment	Temperature range: Operational 0°C to 40°C; storage -25°C to 70°C; Max. rel. humidity 10 - 95% (non condensing)
Protection Class	IP20
Power supply	Internal power supply 110-240V 1.5 A, with energy efficient switching controller; complies with EuP directive 2008/28/EC
Power consumption (idling)	Less than 5 Watt
Housing	Metal case, opening for Kensington lock, prepared for wall mounting
Dimension	Ca. 265 mm x 40 mm x 170 mm (W x H x D)
Fan	Fanless design therefor high MTBF
Reset button	Restart or reset to factory state possible
Function Button	Supported from Release 9.1.10
Standards and certifications	R&TTE directive 1999/5/EG; EN 55022; EN 55024 + EN 55024/A1; EN61000-3-2; EN 61000-3-3; EN 61000-4-4; EN 60950-1; EN 300 328; EN 301 489-17; EN 301 489-1; EN 301 893

## Content of Delivery

19" brackets and screws	Two 19" brackets for the switch panel mounting
Safety Instructions	Safety Instructions
Ethernet cable	1 Ethernet cable, 2m
Power cable	Power Plug 100-240V / 1,5 A
Installation Poster	Guide for the Installation
VDSL/ADSL cable	VDSL/ADSL cable (RJ45-RJ11), 3m

## VPN

Number of VPN tunnels	Inclusive 5 active VPN tunnels with the protocols IPSec, PPTP, L2TP and GRE v.0 (also in combination possible). Optional router extension up to 30 simultaneous utilisable VPN tunnel via license.
PPTP (PAC/PNS)	Point to Point Tunneling Protocol for establishing fo Virtual Privat Networks, inclusive strong encryption methods with 128 Bit (MPPE) up to 168 Bit (DES/3DES, Blowfish)
GRE v.0	Generic Routing Encapsulation V.0 according RFC 2784 for common encapsulation
L2TP	Layer 2 tunnelling protocol inclusive PPP user authentication
IPSec	Internet Protocol Security establishing of VPN connections
IPSec Algorithms	DES (64 Bit), 3DES (192 Bit), AES (128,192,256 Bit), CAST (128 Bit), Blowfish (128-448 Bit), Twofish (256 Bit); MD-5, SHA-1, RipeMD160, Tiger192 Hashes
IPSec hardware acceleration	Integrated hardware acceleration for IPSec encryption algorithms DES, 3DES, AES



<b>VPN</b>	
IPSec IKE	IPSec key exchange via preshared keys or certificates
IPSec IKE Config Mode	IKE Config Mode server enables dynamic assignment of IP addresses from the address pool of the company. IKE Config Mode client enables the router, to get assigned dynamically an IP address.
IPSec IKE XAUTH (Client/Server)	Internet Key Exchange protocol Extended Authenticaion client for login to XAUTH server and XAUTH server for logging of XAUTH clients
IPSec IKE XAUTH (Client/Server)	Inclusive the forwarding to a RADIUS-OTP (One Time Password) server (supported OTP solutions see <a href="http://www.bintec-elmeg.com">www.bintec-elmeg.com</a> ).
IPSec NAT-T	Support of NAT-Traversal (Nat-T) for the application at VPN lines with NAT
IPSec IPComp	IPSec IPComp data compression for higher data throughput via LZS
IPSec certificates (PKI)	Support of X.509 multi-level certificates compatible to Microsoft and Open SSL CA server; upload of PKCS#7/8/10/12 files via TFTP, HTTP, LDAP, file upload and manual via FCI
IPSec SCEP	Certificates management via SCEP (Simple Certificate Enrollment Protocol)
IPSec Certificate Revocation Lists (CRL)	Support of remote CRLs on a server via LDAP or local CRLs
IPSec Dead Peer Detection (DPD)	Continuous control of IPSec connection
IPSec dynamic IP via ISDN	Transmission of dynamic IP address in ISDN D or B channel; free-of-charge licence necessary
IPSec dynamic DNS	Enables the registering of dynamic IP addresses by a dynamic DNS provider for establishing a IPSec connection.
IPSec RADIUS	Authentication of IPSec connections at a RADIUS server. Additionally the IPSec peers, which were configured on a RADIUS server, can be loaded into the gateway (RADIUS dialout).
IPSec Multi User	Enables the Dial-in of several IPSec clients via a single IPSec peer configuration entry
IPSec QoS	The possibility to operate Quality of Service (traffic shaping) inside of an IPSec tunnel
IPSec NAT	By activating of NAT on an IPSec connection it is possible, to implement several remote locations with identical local IP address networks in different IP nets for the VPN connection
Number of IPSec tunnels	Inclusive 5 active IPSec tunnels (expandable to 30 tunnels)

<b>Security</b>	
NAT/PAT	Symmetric Network and Port Address Translation (NAT/PAT) with randomly generated ports inclusive Multi NAT (1:1 translation of whole networks)
Policy based NAT/PAT	Network and Port Address Translation via different criteria like IP protocols, source/destination IP Address, source/destination port
Policy based NAT/PAT	For incoming and outgoing connections and for each interface variable configurable
Content Filtering	Optional ISS/Cobion Content filter (30 day test license inclusive)
Stateful Inspection Firewall	Packet filtering depending on the direction with controlling and interpretation of each single connection status
Packet Filter	Filtering of IP packets according to different criteria like IP protocols, source/destination IP address, source/destination port, TOS/DSCP, layer 2 priority for each interface variable configurable

## Logging / Monitoring / Reporting

Internal system logging	Syslog storage in RAM, display via web-based configuration user interface (http/https), filter for subsystem, level, message
External system logging	Syslog, several syslog server with different syslog level configurable
E-Mail alert	Automatic E-Mail alert by definable events
SNMP traps	SNMP traps (v1, v2, v3) configurable
IPSec monitoring	Display of IPSec tunnel and IPSec statistic; output via web-based configuration user interface (http/https)
Interfaces monitoring	Statistic information of all physical and logical interfaces (ETH0, ETH1, SSIDx, ...), output via web-based configuration user interface (http/https)
IP accounting	Detailed IP accounting, source, destination, port, interface and packet/bytes counter, transmission also via syslog protocol to syslog server
RADIUS accounting	RADIUS accounting for PPP, PPTP, PPPoE and ISDN dialup connections
Keep Alive Monitoring	Control of hosts/connections via ICMP polling
Tracing	Traces can be stored in PCAP format, so that import to different open source trace tools (e.g. Wireshark) is possible.

## Administration / Management

RADIUS	Central check of access authorization at one or several RADIUS server, RADIUS (PPP, IPSec inclusive X-Auth and login authentication)
RADIUS dialout	On a RADIUS server configured PPP und IPSec connection can be loaded into the gateway (RADIUS dialout).
TACACS+	Support of TACACS+ server for login authentication and for shell command authorization
Time synchronization	The device system time can be obtained via ISDN and from a SNTP server (up to 3 time server configurable). The obtained time can also be transmitted per SNTP to SNTP clients.
Automatic Time Settings	Time zone profiles are configurable. That enables an automatic change from summer to winter time.
Supported management systems	DIME Manager, XAdmin
Configurable scheduler	Configuring of time and event controlled tasks, e.g. reboot device, activate/deactivate interface, activate/deactivate WLAN, trigger SW update and configuration backup
Configuration Interface (FCI)	Integrated web server for web-based configuration via HTTP or HTTPS (supporting self created certificates). This user interface is by most of bintec elmeg GmbH products identical.
Software update	Software updates are free of charge; update via local files, HTTP, TFTP or via direct access to the bintec elmeg web server
Remote maintenance	Remote maintenance via telnet, SSL, SSH, HTTP, HTTPS and SNMP (V1,V2,V3)
GSM remote maintenance	Remote maintenance via GSM login (external USB UMTS (3G) modem required)
Device discovery function	Device discovery via SNMP multicast.

## Administration / Management

On The Fly configuration	No reboot after reconfiguration required
SNMP	SNMP (v1, v2, v3), USM model, VACM views, SNMP traps (v1, v2, v3) configurable, SNMP IP access list configurable
SNMP configuration	Complete management with MIB-II, MIB 802.11, Enterprise MIB
Configuration export and import	Load and save configurations, optional encrypted; optional automatic control via scheduler
SSH login	Supports SSH V1.5 and SSH V2.0 for secure connections of terminal applications
HP OpenView	Integration into Network Node Manager
XAdmin	Support of XAdmin roll out and configuration management tool for larger router installations (IP+ISDN+GSM)
Configuration via USB	Configuration interface is available

## Accessoires

### WLAN Controller

<b>License WLAN Contr. 6AP</b> (5500000943)	WLAN Controller license for 6 Access Points (APs) or for the extension with 6 APs for the products: RS123x, RS353xx. Rxxx2 and RXL12x00.
---	--

### Software Licenses

<b>RSxx3/Rxx02/RTxx02/RXL-IPSEC25</b> (5500000781)	Additional 25 IPSec tunnel license for RSxx3, Rxx02, RTxx02 and RXL12xxx series
<b>VDSL License RS353ax (Annex A)</b> (5500001622)	VDSL license for RS353a/aw (Annex A, ADSL over POTS)
<b>BRRP-RS123x/RS35x-Series</b> (5500001630)	Software License for bintec Router Redundancy Protocol (BRRP) for RS123x and RS35x-series
<b>Cobion Content Filter Small</b> (80551)	Cobion content filter for RSxxx, Rxx02, RTxx02 series; R230a(w), R232b(w), TR200, R1200(w/wu), R3000(w), R3400, R3800, R232aw, RV-Series; list price for one year

### Pick-up Service / Warranty Extension

<b>Service Package 'small'</b> (5500000810)	Warranty extension of 3 years to a total of 5 years, including advanced replacement for bintec elmeg products of the category 'small'. Please find a detailed description as well as an overview of the categories on <a href="http://www.bintec-elmeg.com/servicepackages">www.bintec-elmeg.com/servicepackages</a> .
---	--

### Product Services

<b>HotSpotHosting 2yr 1 location</b> (5500000861)	HotSpot solution hosting fee for 2 year and 1 location
<b>HotSpotHosting 1yr 1 location</b> (5510000198)	HotSpot solution hosting fee for 1 year and 1 location

## Product Services

<b>Additional HotSpot location</b> (5510000199)	Additional location for the HotSpot solution (551000198, 5500000861) valid for one year
---	---

## Add-ons

<b>bintec 4GE-LE</b> (5530000119)	LTE (4G)/UMTS (3G) extension device for router; 1x Gbit Eth; Simcard slot; Wallmounting; PoE Injector inclusive
-----------------------------------	---